


GAMA LIGERA EFI

15 HP



	F15ABML-EFI	F15ABMS-EFI	F15ABWL-EFI	F15ABWS-EFI	F15AFWL-EFI	F15AFWS-EFI
A (mm)	988 (38.9")		988 (38.9")		665 (26.2")	
B (mm)	420 (16.5")		420 (16.5")		430 (16.9")	
C (mm)	1.197 (47.1")	1.070 (42.1")	1.197 (47.1")	1.070 (42.1")	1.197 (47.1")	1.070 (42.1")
D (mm)	508 (20.0")	381 (15")	508 (20.0")	381 (15")	508 (20.0")	381 (15")
	53.7 kg	51.7 kg	55.7 kg	53.7 kg	54.7 kg	52.7 kg

		15 HP			
Full throttle operating range		5.300 - 6.000 rpm			
Maximum output		11 Kw 5.500 rpm			
Idling speed (neutral)		1.000 - 1.100 rpm			
Engine type		SOHC			
Cylinders		L2			
Displacement		362 cm ³			
Bore per stroke		63 x 58.1 mm (2.48" x 2.29")			
Ignition system		CDI			
Fuel delivery system		EFI			
Alternator		12V 6A			
Control system					
Starting system					
Gear positions		F - N - R			
Gear ratio		1.85 (24/13)			
Trim & tilt system					
Maximum fuel waste		5.4 L/h			
Fuel tank capacity		24 L			
Engine oil capacity		1.7 L			
Gear oil capacity		430 cm ³			
Included STD Propeller		3-9 ^{1/4} " x 11"			



F15ABML-EFI

- Standard rotation
- HP
- Tiller control
- MANUAL start
- Long Shaft 508 mm / 20"
- EFI

F15ABWS-EFI

- Standard rotation
- HP
- Tiller control
- Electrical start
- Short Shaft 381 mm / 15"
- EFI

F15AFWL-EFI

- Standard rotation
- HP
- REMOTE control
- Electrical start
- Long Shaft 508 mm / 20"
- EFI

	UN.	UN.
Owner manual	1	1
Stoper, hang rope assy	1	1
Emergency handle-start rope	1	1
Screwdrive	1	1
Spark plug	2	2
Spark plug sleeve	1	1
Pin, cotter	1	1
Oil cleaner	1	1
Fuel line assy	1	1
Fuel tank assy	1	1
Control box assy		1
Control cable assy		2
Link rod, turning		1

INCLUDED ACCESSORIES






PROPELLERS



	D	P	REF	DESC.
15 HP	9 ¹ / ₄	7	SOL3111-093-07	OP
	9 ¹ / ₄	8	SOL3111-093-08	OP
	9 ¹ / ₄	9	SOL3111-093-09	OP
	9 ¹ / ₄	10	SOL3111-093-10	OP
	9 ¹ / ₄	11	PAF15-06090000	STD
	9 ¹ / ₄	12	SOL3111-093-12	OP



B	A	D	P	R	OP	STD
Blades	Tooth Spline	Diameter	Pitch	Rotation: L (left) R (Right)	Optional	Standard



OIL	REF
10W30 10W40 NMMA approved engine oil	REC10W30U3
	REC10W30U6
	REC10W40U3
	REC10W40U6
80W90 Synthetic marine transmission oil GL-5 approved	REC80W90U3
	REC80W90U6

