


GAMA MEDIA EFI

60 - 50 HP



	60 HP	50 HP
	F60FEL-T-EFI	F50FEL-T-EFI
A (mm)	713 (28")	713 (28")
B (mm)	427 (16.8")	427 (16.8")
C (mm)	1.435 (56.5")	1.435 (56.5")
D (mm)	508 (20")	508 (20")
	113 kg	113 kg
Full throttle operating range	5.300 – 6.000 rpm	5.300 – 6.000 rpm
Maximum output	44.1 Kw 60 Hp 5.500 rpm	36.8 Kw 50 Hp 5.500 rpm
Idling speed (neutral)	750 - 850 rpm	750 - 850 rpm
Engine type	SOHC (8 valves)	SOHC (8 valves)
Cylinders	L4	L4
Displacement	996 cm ³	996 cm ³
Bore per stroke	65 mm x 75 mm (2.56" x 2.95")	65 mm x 75 mm (2.56" x 2.95")
Ignition system	CDI	CDI
Fuel delivery system	EFI	EFI
Alternator	12V 35A	12V 35A
Control system		
Starting system		
Gear positions	F - N - R	F - N - R
Gear ratio	1.85 (24/13)	1.85 (24/13)
Trim & tilt system	TRIM	TRIM
Maximum fuel waste	18.5 L/h	18 L/h
Fuel tank capacity	24L	24L
Engine oil capacity	2.5 L	2.5 L
Gear oil capacity	430 cm ³	430 cm ³
Included STD Propeller	3-11 ^{1/2} x 13"	3-11 ^{1/2} x 13"



F60FEL-T-EFI




	UN.	INCLUDED ACCESSORIES
Owner manual	1	
Stoper, hang rope assy	1	
Emergency handle-start rope	1	
Screwdrive	1	
Spark plug	4	
Spark plug sleeve	1	
Pin, cotter	1	
Oil cleaner	1	
Fuel line assy	1	
Fuel tank assy	1	
Control box assy	1	
Control cable assy	2	
Link rod, turning	1	
Tachometer	1	
Trim gauge	1	



PROPELLERS



	D	P	REF	DESC.
50 HP 60 HP	11 ^{3/4}	12	SOL3311-114-12	OP
	11 ^{1/2}	13	PAT40-04070000	STD
	11 ^{1/4}	14	SOL3311-111-14	OP



B	A	D	P	R	OP	STD
Blades	Tooth Spline	Diameter	Pitch	Rotation: L (left) R (Right)	Optional	Standard



OIL	REF
10W30 10W40 NMMA approved engine oil	REC10W30U3
	REC10W30U6
	REC10W40U3
	REC10W40U6
80W90 Synthetic marine transmission oil GL-5 approved	REC80W90U3
	REC80W90U6

